

## E-Vision Laser 5000 WUXGA (Preliminary)

5,000 ANSI / 5,500 ISO Lumens | Contrast Ratio: 20,000:1 (Dynamic Black) | Part No:118-568

### E-VISION LASER 5000 DIGITAL PROJECTOR



THE VISIONARIES CHOICE

**Colour System:**

Laser Phosphor

**DMD Specification:**

1920 x 1200 pixels native resolution.  
Fast transit pixels for smooth greyscale and improved contrast.

**Display Type:**

1 x 0.67" DarkChip™ DMD™

**Aspect Ratio:**

16x10

**Fill Factor**

### Key Features

#### Video & Graphics Processing

- HDMI 1.4a for Side by Side, Frame Packing, Frame Sequential & Top Bottom 3D formats.
- Synchronisation of active 3D glasses.
- DICOM simulation mode.
- Mobile High-Definition Link (MHL™) connection allows mirrored content from smartphones, tablets and other portable consumer electronics devices.

#### Geometry Correction

- Vertical & Horizontal Keystone correction (2D: Vertical  $\pm 30^\circ$ , Horizontal  $\pm 30^\circ$ ).
- Four Corner adjustment.
- Selectable 16:9, 4:3, Native, Letterbox and Full Screen aspect ratios.
- Digital Zoom +10~-10.

#### HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.
- HDBaseT® includes audio, Ethernet 100BaseT and RS232/IR control.

#### Colour Processing

- 2 x speed, 3 Segment (GBY) Phosphor wheel.
- 2 x 120Hz speed, 4 Segment (RGBY) Colour wheel.
- 10-bit colour display.
- 55% of NTSC colour gamut.

**Source Compatibility:**

Graphics standards up to 1920 x 1200 resolution at 60Hz.  
Horizontal frequency 15, 31 ~ 102kHz.  
Vertical frequency 24 ~ 30Hz, 47 ~ 120Hz.

## Inputs/Outputs

Video & Computer			Communication & Control		
<b>Type</b>	<b>Connector</b>	<b>Qty</b>	<b>Type</b>	<b>Connector</b>	<b>Qty</b>
HDMI 1.4a	HDMI	2	LAN	8P8C (RJ45)	1
HDMI 1.4a + MHL	HDMI	1	RS-232C	9-pin D-sub	1
VGA / Analog RGB	15-pin D-Sub	1	USB (for Service)	Mini B	1
VGA / Monitor Out	15-pin D-Sub	1	3D Sync Out	VESA 3-PIN mini	1
Composite Video	RCA	1		DIN	
HDBaseT	8P8C (RJ45)	1	<b>NOTE: The HDBaseT and LAN ports are not shared.</b>		
USB Type A / (5V/1.5A)	USB Type A	1			
<b>NOTE: The USB is to power WHDI™ interfaces.</b>					
<b>Audio:</b>					
Audio IN L+R	Phono	2			
Audio IN L+R	Stereo 3.5 mm	1			
Mic IN	jack	1			
Audio OUT (variable)	3.5 mm jack	1			
Speakers	Stereo 3.5 mm	2			
	jack				
	5W speaker				
<b>3D Formats Supported</b>			<b>HDTV Formats Supported</b>		
Frame Packing			1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50, 60Hz)		
HQFS Frame Sequential					
Side By Side (half)					
Top and Bottom					
<b>Computer Compatibility</b>			<b>Bandwidth</b>		
VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac					
<b>Remote Control</b>			<b>Automation Control</b>		
IR remote control, 2 x IR receivers (front sensitivity up to 7m, rear sensitivity up to 10m)			LAN control - Crestron RoomView® Connected		
			LAN control - Crestron eControl		
			LAN control - Extron		
			LAN control - AMX SSDP		
			LAN control to RS232 by Telnet		
			Concurrence Control for RS232/LAN		
			HDBaseT communication		
			Projector status email alerts		
<b>Colour Temperature</b>					
Warm / Normal / Cold					
<b>Lamp Type</b>			<b>Typical Lamp Life</b>		
Laser Light Source			20,000 hours		
<b>Lenses</b>					
<b>Lens</b>	<b>Part No.</b>	<b>Focus Range</b>	<b>Lens Shift</b>		
1.15 - 1.90 :1 zoom	N/A	1.5m - 5.0m	Vert: Fixed Offset 0.575 (U) frame + small variable shift. See User manual. Hor: 0.025(L) 0.025 (R) frame		
<b>Lens Mount</b>					
Manual zoom and focus with horizontal and vertical shift.					
<b>Mechanical Mounting</b>			<b>Orientation</b>		

Front/Rear  
Front/Rear Ceiling  
Two adjustable front feet, 10° (43mm)  
Ceiling Mount compatible chassis with 7 off M4 mounting holes available, maximum screw length 12mm (0.47")

**Table Top or Inverted:** Yes

**Pointing Up:** Yes

**Pointing Down:** Yes

**Roll (Portrait):** Yes

#### Power Requirements

100-240VAC 50/60Hz single phase

#### Power Consumption

Normal Mode (100%) 440W @230V 460W @110V  
Eco Mode (80%) 340W @230V 360W @110V  
Dimmy Mode (40%) 190W @230V 200W @110V  
Standby, LAN enabled Standby, LAN disabled

#### Thermal Dissipation

Normal Mode (typical):  
1570 BTU/Hour @ 110VAC  
1501 BTU/Hour @ 230VAC BTU/Hour

#### Fan Noise

Normal Mode Typ: 36 dBA / Max: 38 dBA  
Eco Mode Support Typ: 34 dBA / Max: 36 dBA  
Eco Plus Mode Typ: 34 dBA / Max: 36 dBA  
Dimmy Mode Typ: 29 dBA / Max: 31 dBA  
Extreme Dimmy Mode Typ: 29 dBA / Max: 31 dBA

#### Operating/Storage Temperature

Operating: 0° to 40°C (32F to 104F)  
Storage: -20° to 60°C (-4F to 140F)  
Altitude: 2,500ft to 5,500ft at a maximum of 30°C (86F)  
Altitude: 5,500ft to 10,000ft at a maximum of 25°C (77F)

#### Operating Humidity

10 to 85% non-condensing

#### Weight (Chassis Only)

10.7 kg  
23.6 lb

#### Dimensions

L: 45.0 cm W: 35.0 cm H: 15.1 cm  
L: 17.7 in W: 13.8 in H: 5.9 in

#### Safety & EMC Regulations

UL/cUL, CB, CCC/CECP, FCC Class B, FDA, CE  
IEC 60825-1:2007 3R  
IEC60825-1:2014 Class 1  
IEC EN 62471-5 Risk Group 2

#### Accessories

Accessory	Part No.
Infrared Remote (replacement)	118-678

*\*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.*

#### Downloads

[User Guides](#)

[User Guides German](#)

[User Guides French](#)

[Important Information](#)



Certificate Number 13629  
ISO 9001

Specifications subject to change without notice. Digital Projection version: - ©2016 Digital Projection.  
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

**DIGITAL PROJECTION, INC** 55 CHASTAIN ROAD, SUITE 115 KENNESAW, GA. 30144  
T: 770.420.1350 | F: 770.420.1360 | [www.digitalprojection.com](http://www.digitalprojection.com)

**DIGITAL PROJECTION, CHINA** Rm A2006, ShaoYaoJu 101 North lane, Shi AO International Center, Chao Yang District, Beijing, 100029, PR  
CHINA  
T: +86.10.58239771 | F: +86 10 58239770

**DIGITAL PROJECTION, ASIA** 16 NEW INDUSTRIAL ROAD, #02-10 HUDSON TECHNOCENTRE SINGAPORE 536204  
T: +65.6284.1138 | F: +65.6284.1238