

## E-Vision Laser 13000 WU

12,000 ANSI / 13,500 ISO Lumens | Contrast Ratio: 10,000:1 (Dynamic Black) 1,000:1 native | Part No:119-734

## E-VISION LASER 13000 WU DIGITAL PROJECTOR



THE VISIONARIES CHOICE

### Colour System:

Blue and Red Lasers with Phosphor wheel and 3-segment colour wheel

### DMD Specification:

1920 x 1200 pixels native display.  
Fast transit pixels for smooth greyscale and improved contrast.

### Display Type:

1 x 0.67" DarkChip™ DMD™

### Aspect Ratio:

16x10

### Fill Factor

87%

## Key Features

### Red Laser Assist

- Uses blue and red laser diodes for increased colour fidelity and highly accurate colours

### Video & Graphics Processing

- HDMI 1.4b for Side by Side, Frame Packing, Frame Sequential & Top Bottom 3D formats.
- Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources
- Dual Pipe Processing: Two sources in parallel for Left and Right eyes.
- Synchronisation of active glasses.
- 3GSDI with loop-through.
- 24p and 1080p native display.
- DICOM simulation mode.

### Geometry Correction

- Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, and Image Rotation.
- Blanking control for custom input window sizing.
- Scaling for fixed aspect ratio screens.

### Edge Blending

- For independent edge and blend width adjustment.

### Picture in Picture

- Two sources can be displayed either one within the other (PIP), or side by side, with original aspect ratios maintained.

### HDBaseT® Interface

- Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable.

- Allows the projector to be placed up to 100m from the source with low cost cabling.

## Colour Processing

- Powerful seven point colour correction for accurate colour matching.

## Projector Controller Software

- Intuitive user interface for network control
- Simultaneous control of user-defined groups of projectors
- At-a-glance monitoring of projector status

## Projector Automation

- Real-time clock provides daily on/off automation.

## Projector Maintenance Features

- Sealed optics.
- Long life 20,000 hour illumination.

### Source Compatibility:

3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.  
 HDMI including Deep Color™ processing.  
 Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI, DisplayPort or VGA.  
 Component Video (SD and HD) via RGBHV.

## Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
DVI-D 1.0	DVI	1	3D Sync Out	BNC	1
DisplayPort 1.1a	DisplayPort	1	3D Sync In	BNC	1
HDMI 1.4b	HDMI	2	LAN	RJ45	1
3G-SDI in	BNC	1	RS232	9-pin D-Sub	1
3G-SDI out	BNC	1	Wired Remote	3.5mm Stereo Jack	1
VGA / Analog RGB	15-pin D-Sub	1	12V Trigger	3.5mm Stereo Jack	2
VGA Monitor out	15-pin D-Sub	1			
Component Video	5 x BNC	1			
HDBaseT (see LAN)	LAN RJ45	1			

**NOTE: The LAN port is shared with HDBase-T.**

3D Formats Supported	HDTV Formats Supported
Frame Packing Dual Pipe Frame Sequential Side By Side (half) Top and Bottom	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50, 60Hz)

Computer Compatibility	Bandwidth
Up to 1920 x 1200	165 MHz on analog RGB 165 Megapixels per second on HDMI

Remote Control	Automation Control
Addressable IR remote control, wireless and wired. On-Board keypad.	Crestron RoomView® Connected PJLink Class 1 LAN RS-232 AMX (Device Discovery) Served web page

Colour Temperature	Operation
3200 to 9300K	24x7 Operation

Lamp Type	Typical Lamp Life
Blue and Red Laser Light Source	20,000 hours

### Lenses

Lens	Part No.	Optimised Focus	Lens Shift
0.38 :1 fixed	117-341	0.68m - 2.44m	none
0.76 :1 fixed	112-499	0.81m - 5.08m	none
0.75 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
1.25 - 1.79 :1 zoom	112-500	1.33m - 11.73m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
1.73 - 2.27 :1 zoom	112-501	1.83m - 14.9m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
2.22 - 3.67 :1 zoom	112-502	2.36m - 24.2m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
3.58 - 5.38 :1 zoom	112-503	3.8m - 35.35m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
5.31 - 8.26 :1 zoom	112-504	5.59m - 54.8m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame

\* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,

### Lens Mount

Motorised and programmable shift, zoom and focus.  
Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).

Mechanical Mounting	Orientation
---------------------	-------------

Front/Rear Table	<b>Table Top or Inverted:</b> Yes
Front/Rear Ceiling	<b>Pointing Up:</b> Yes
Adjustable Front/Rear Feet	<b>Pointing Down:</b> Yes
	<b>Roll (Portrait):</b> Yes

Power Requirements	Power Consumption
--------------------	-------------------

200-240VAC 50/60Hz single phase 7.8A	Typical 1470W @ 240VAC in Normal mode
	Typical 1220W @ 240VAC in ECO mode
100-130VAC 50/60Hz single phase 11.5A	Typical 1510W @ 240VAC in High Altitude mode
<b>Note: that in 100-130VAC operation, the projector will be at 70% brightness</b>	Typical 1060W @ 110VAC in Normal mode
	Typical 1050W @ 110VAC in ECO mode
	Typical 1110W @ 110VAC in High Altitude mode W

Thermal Dissipation	Fan Noise
---------------------	-----------

Typical 5016 BTU/Hour @ 240VAC in Normal mode	Normal mode: 48 dBA Max, 46 dBA Typical
Typical 4163 BTU/Hour @ 240VAC in ECO mode	Eco mode: 44 dBA Max, 42 dBA Typical
Typical 5152 BTU/Hour @ 240VAC in High Altitude mode	High Altitude Normal mode: 59 dBA Max, 57 dBA Typical
Typical 3617 BTU/Hour @ 110VAC in Normal mode	High Altitude Eco Mode: 59 dBA Max, 57 dBA Typical
Typical 3583 BTU/Hour @ 110VAC in ECO mode	
Typical 3787 BTU/Hour @ 110VAC in High Altitude mode	
BTU/Hour	

Operating/Storage Temperature	Operating Humidity
-------------------------------	--------------------

Operating: 0 to 35C (32 to 95F)	10 to 90% relative, non-condensing
Operating: 35 to 40C (95 to 104F) w/ reduced light output	
Storage: -20 to 60C (-4 to 140F)	

Weight (Chassis Only)	Dimensions
-----------------------	------------

31 kg	L: 59.83 cm x W: 50 cm x H: 21.85 cm
68.3 lb	L: 23.55 in x W: 19.68 in x H: 8.60 in

### Safety & EMC Regulations

UL / cUL, BIS, CB, CCC, KC, FCC (Part 15) Class A, FDA (Accession Number), CE, RoHS 2, IEC EN 60825-1-2014 Class 3R Laser Product, IEC EN 60825-1-2007 Class 1 Laser Product IEC EN 62471-5-2015 Risk Group 3

### Accessories

Accessory	Part No.
Infrared Remote (replacement)	117-780

\*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.

### Downloads

[PDF CAD Drawings](#)

[AUTOCAD Drawings](#)

[User Guides](#)

[User Guides German](#)

[User Guides French](#)

[Important Information](#)



Certificate Number 13629  
ISO 9001

---

Specifications subject to change without notice. Digital Projection version: - ©2016 Digital Projection.  
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

---

**DIGITAL PROJECTION, LTD** GREENSIDE WAY, MIDDLETON MANCHESTER, UK. M24 1XX  
T: +44.161.947.3300 | F: +44.161.684.7674 | [www.digitalprojection.co.uk](http://www.digitalprojection.co.uk)

**DIGITAL PROJECTION, INC** 55 CHASTAIN ROAD, SUITE 115 KENNESAW, GA. 30144  
T: 770.420.1350 | F: 770.420.1360 | [www.digitalprojection.com](http://www.digitalprojection.com)

**DIGITAL PROJECTION, CHINA** Rm A2006, ShaoYaoJu 101 North lane, Shi AO International Center, Chao Yang District, Beijing, 100029, PR CHINA  
T: +86.10.58239771 | F: +86 10 58239770

**DIGITAL PROJECTION, ASIA** 16 NEW INDUSTRIAL ROAD, #02-10 HUDSON TECHNOCENTRE SINGAPORE 536204  
T: +65.6284.1138 | F: +65.6284.1238