

[Click to Print This Page](#)



TITAN LASER SERIES DIGITAL PROJECTORS

THE VISIONARIES CHOICE



Titan 47000 WU (Preliminary)

47,000 ISO / 42,000 ANSI Lumens | Contrast Ratio: 18,000:1 (Dynamic Black) / 2,000:1 Native | Part Number: 121-653

Key Specifications:

Colour System:	Laser Phosphor with ColorBoost+Red Laser
Display Type:	3 x 0.96" WUXGA DMD™
DMD Specification:	Display capability up to WUXGA Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16:10
Fill Factor	87%
Key Features:	Video & Graphics Processing <ul style="list-style-type: none">• HDMI 2.0 compliance for Side by Side, Frame Packing, Frame Sequential and TopBottom 3D Formats.• DisplayPort 1.2 with HDCP 2.2 compliance.• 10-bit colour processing (30-bits per pixel).• Support for 1080p 24Hz native display.• Support for 4K 4096 x 2160 resolution. Output will be scaled to WUXGA• HDR support• Input source automatically detected.• Input redundancy mode with auto switching.• Dual Pipe Processing: Two sources in parallel for Left and Right eyes.• Synchronisation of active 3D glasses or polarising switcher.• DICOM simulation mode.• Sealed light engine

General Features

- Constant Brightness control
- Multi Projector brightness and colour control.
- Compatible with selected 3rd party lenses via lens converter
- Selectable EDID
- Custom Start-up Logo
- Smear Reduction (fast frame) (2D Only)
- Electronic PIC MUTE with selectable fade in/out timers
- On board 4 -line LCD display for at a glance status

Geometry Correction

- Vertical & Horizontal Keystone correction.
- Four Corner adjustment.
- Rotation.
- Pin/Barrel.
- Wall Corner adjustment.
- Centre Shift (Horizontal and Vertical linearity adjustment).
- Custom Warp.
- Upload of maps for warp, blend, uniformity and masking.
- Selectable aspect ratios: 5:4 / 4:3 / 16:10 /16:9 / 1.88 / 2.35 / TheaterScope / Source / Unscaled.
- Digital Zoom.
- Blanking control for custom input window sizing.

Edge Blending

- Blending control available for all sides with width control.
- Correction for non-active pixels at the edge of the display.
- Electronic Black Level Compensation.
- Upload of Blend Maps including Blend, Uniformity, Masking, Pixel by Pixel

HDBaseT® Interface

- Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable
- Allows projector to be placed up to 100m from source with low cost cabling
- Supports up to 4K 4096 x 2160@60Hz 4:2:0 or 4K 4096 x 2160@30Hz 4:2:2
- Includes Ethernet 100BaseT and RS232/IR control.

Colour Processing

- Four colour modes available
- Powerful seven point colour correction for accurate colour matching with presets.
- Easy colour temperature selection
- Manual seven point colour adjustment
- Traditional lifts and gains

Projector Controller Software

- Intuitive user interface for network control
- Simultaneous control of user-defined groups of projectors
- At-a-glance monitoring of projector status


Projector Automation

- Real-time clock provides daily on/off automation
- E-mail alerts for system status

Installation

- 4 x eye bolts fitted for easy rigging.

	<ul style="list-style-type: none"> 4 x top stacking mounts and mount securing pins supplied as standard accessories. 																																																												
Source Compatibility	<p>2D Graphics standards up to 4K-UHD 3840x2160 resolution at 60Hz via HDMI 2.0b, HDBaseT (4:2:0), DisplayPort inputs</p> <p>3D Graphics standards up to dual-pipe WUXGA 60Hz for input (120Hz output) via HDMI 2.0 and Display Port inputs</p> <p>12G-SDI is SMPTE 259M, 292M, 424M and ST-2082 compliant.</p> <p>WUXGA mode</p> <p>2D sources up to WUXGA 60Hz and 4K-UHD 60Hz can be displayed scaled to fit WUXGA</p> <p>3D sources up to WUXGA 60Hz Input -120Hz output can be displayed scaled to fit WUXGA</p> <p>Auto Mode</p> <p>Sources greater than WUXGA will be displayed scaled to fit WUXGA</p>																																																												
Inputs/Outputs	<table border="1"> <thead> <tr> <th colspan="3">Video & Computer</th> <th colspan="3">Communication & Control</th> </tr> <tr> <th>Type</th> <th>Connector</th> <th>Qty</th> <th>Type</th> <th>Connector</th> <th>Qty</th> </tr> </thead> <tbody> <tr> <td>DisplayPort 1.2a (2D)</td> <td>DisplayPort</td> <td>2</td> <td>3D SYNC IN</td> <td>BNC</td> <td>1</td> </tr> <tr> <td>HDMI 2.0b</td> <td>HDMI</td> <td>2</td> <td>3D Sync Out</td> <td>BNC</td> <td>1</td> </tr> <tr> <td>12G-SDI in</td> <td>BNC</td> <td>1</td> <td>LAN</td> <td>RJ45</td> <td>1</td> </tr> <tr> <td>12G-SDI out</td> <td>BNC</td> <td>1</td> <td>RS-232</td> <td>9-pin D-Sub</td> <td>1</td> </tr> <tr> <td>HDBaseT/LAN</td> <td>RJ45</td> <td>1</td> <td>Wired Remote</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> <tr> <td></td> <td></td> <td></td> <td>12V Trigger</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> <tr> <td></td> <td></td> <td></td> <td>3D Sync IR Out</td> <td>BNC</td> <td>1</td> </tr> <tr> <td></td> <td></td> <td></td> <td>USB 5V 2A</td> <td>Type A</td> <td>1</td> </tr> </tbody> </table>	Video & Computer			Communication & Control			Type	Connector	Qty	Type	Connector	Qty	DisplayPort 1.2a (2D)	DisplayPort	2	3D SYNC IN	BNC	1	HDMI 2.0b	HDMI	2	3D Sync Out	BNC	1	12G-SDI in	BNC	1	LAN	RJ45	1	12G-SDI out	BNC	1	RS-232	9-pin D-Sub	1	HDBaseT/LAN	RJ45	1	Wired Remote	3.5mm Stereo Jack	1				12V Trigger	3.5mm Stereo Jack	1				3D Sync IR Out	BNC	1				USB 5V 2A	Type A	1
Video & Computer			Communication & Control																																																										
Type	Connector	Qty	Type	Connector	Qty																																																								
DisplayPort 1.2a (2D)	DisplayPort	2	3D SYNC IN	BNC	1																																																								
HDMI 2.0b	HDMI	2	3D Sync Out	BNC	1																																																								
12G-SDI in	BNC	1	LAN	RJ45	1																																																								
12G-SDI out	BNC	1	RS-232	9-pin D-Sub	1																																																								
HDBaseT/LAN	RJ45	1	Wired Remote	3.5mm Stereo Jack	1																																																								
			12V Trigger	3.5mm Stereo Jack	1																																																								
			3D Sync IR Out	BNC	1																																																								
			USB 5V 2A	Type A	1																																																								
3D Formats Supported	<p>Sequential / 1080p @100Hz</p> <p>Sequential / 1080p @120Hz</p> <p>Dual-Pipe / 1080p @ 50Hz per eye</p> <p>Dual-Pipe / 1080p @ 60Hz per eye</p> <p>Dual-Pipe / WUXGA @ 60Hz</p> <p>Also supports mandatory formats including side by side, top/bottom and frame packing</p>																																																												
HDTV Formats Supported	<p>1080p (23.98Hz, 24Hz, 25Hz, 29.97Hz, 30Hz, 50Hz, 59.94Hz, 60Hz).</p> <p>1080i (50Hz, 59.94Hz, 60Hz).</p> <p>720p (50Hz, 59.94Hz, 60Hz).</p> <p>4K-UHD (23.97Hz, 24Hz, 25Hz, 29.97Hz, 30Hz, 50Hz, 60Hz) (Output will be scaled to WUXGA).</p>																																																												
Computer Compatibility	<p>2D 4K-UHD up to 60Hz (Output will be scaled to WUXGA)</p> <p>3D Supported Formats will be displayed up to WUXGA</p>																																																												
Bandwidth	18Gb/s (600MHz clock rate) on HDMI																																																												
Remote Control	Addressable IR remote Control, Wireless and wired. On-Board keypad																																																												
Automation Control	<p>LAN</p> <p>RS-232</p> <p>Alert E-Mails from Projector</p> <p>Served webpage OSD functions for full Projector Control via web browser</p> <p>LAN Control-Crestron Roomview™</p> <p>LAN Control-Crestron eControl</p> <p>LAN Control-PJ Link compatible</p> <p>LAN Control-AMX SSDP</p> <p>LAN to RS232 (RS232 by Telnet)</p> <p>Concurrence Control for RS232/LAN</p> <p>DMX Art-Net control</p> <p>Scheduled On and Off times</p>																																																												
Colour Temperature	3200K to 9300K																																																												

Operation	 The logo features a stylized orange clock face with a single hand pointing to the top, positioned above the text "24x7" in a large, bold font, and "OPERATION" in a smaller font below it.
illumination Type	Laser Light Source
Typical illumination Life	20,000 Hours (Normal Mode) 40,000 Hours (ECO Mode)

Lenses	Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)
	0.37:1 (Right Angled)	120-510	1.6m - 4.9m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.31 (L) 0.31 (R) frame
	0.65-0.85:1 (Right Angled)	120-511	2.8m - 8.4m	Vert: 0.51 (U) 0.51 (D) frame, Hor: 0.24 (L) 0.24 (R) frame
	0.8-1.16:1 (Includes support bracket)	120-827	1.7m - 11m	Vert: 0.4 (U) 0.4 (D) frame, Hor: 0.19 (L) 0.19 (R) frame
	0.67:1 fixed HB	105-607	1.1m - 10m	Vert: 0.108 (U) 0.108 (D) frame, Hor: 0.044 (L) 0.044 (R) frame
	1.12:1 (short) fixed HB	105-608	3m - 15m	Vert: 0.567 (U) 0.567 (D) frame, Hor: 0.273 (L) 0.273 (R) frame
	1.16 - 1.49:1 zoom HB	109-236	3m - 15m	Vert: 0.408 (U) 0.408 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
	1.39 - 1.87:1 zoom HB	105-610	4m - 24m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.273 (L) 0.273 (R) frame
	1.87 - 2.56:1 zoom HB	105-611	4m - 24m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.273 (L) 0.273 (R) frame
	2.56 - 4.16:1 zoom HB	105-612	9.1m - 45m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.273 (L) 0.273 (R) frame
	4.16 - 6.96:1 zoom HB	105-613	12m - 80m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.273 (L) 0.273 (R) frame
	6.92 - 10.36:1 zoom HB	109-235	12m - 80m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.273 (L) 0.273 (R) frame
	<p>* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,</p>			
Lens Mount	Motorised Shift, Zoom and Focus. Intelligent Lens Memory with 10 user-definable pre-set positions for zoom lenses.			
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling			

	Adjustable Front/Rear Feet						
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes						
Power Requirements	110V~130Vac/ 50~60Hz 180V~240Vac/ 50~60Hz single phase * Note that in 120V operation, the projector will be at 25% brightness TBC						
Power Consumption	230V Typical: 3650W , Maximum 4000W 110V Maximum: 1080W (TBC)						
Thermal Dissipation	Max 14160.38 BTU/hr @ 200VAC Max 3685 BTU/hr @ 110VAC						
Fan Noise	Max 53 dBA Eco Typ : 50 dBA						
Operating/Storage Temperature Operating:	Operating: Full Power 0°C ~ 35°C (32°F ~95°F), ECO upto 40°C (104°F) Storage: -20°C ~ 60°C (-4°F ~ 140°F)						
Operating Humidity	Operating: 10% ~ 90% non-condensing Storage: 10% ~ 90% non-condensing						
Weight	88 (without lens) kg / 194 (without lens) lbs						
Dimensions	L: 840mm, W: 650mm, H: 381mm (Excl handles) L: 33.1in, W: 25.6in, H: 15in (Excl handles) * See drawings for full details						
Safety & EMC Regulations	TBC						
Accessories	<table border="1"> <thead> <tr> <th>Accessory</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td>Infrared Remote Control (Replacement)</td> <td>118-678</td> </tr> <tr> <td>Optional lens mount insert for selected third party lenses (Contact local sales representative for further information)</td> <td>119-729</td> </tr> </tbody> </table> <p><i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i></p>	Accessory	Part No.	Infrared Remote Control (Replacement)	118-678	Optional lens mount insert for selected third party lenses (Contact local sales representative for further information)	119-729
Accessory	Part No.						
Infrared Remote Control (Replacement)	118-678						
Optional lens mount insert for selected third party lenses (Contact local sales representative for further information)	119-729						
Downloads	PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings						
User Guide							



DIGITAL PROJECTION, LTD



Greenside Way, Middleton Manchester, UK

M24 1XX



T: +44.161.947.3300 | F: +44.161.684.7674



www.digitalprojection.co.uk

DIGITAL  **PROJECTION**

A Delta Group Company

Specifications subject to change without notice.
©2022 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770



Certificate Number 13629
ISO 9001